

Glazed Ceramic Tiles

Definition

Ceramic with glazed surface

Ecology

The recommended products were specially developed for the requirements of natural and artificial stone. Quality, effectiveness and environmental protection have been optimized in relation to one another and in accordance with the latest developments in technology. Please apply the product to a suitable sample area in order to establish its effectiveness, the right dilution, the coverage and its exact effect.

Safety

The products comply with the provisions laid down by the law in terms of their labelling and the contained substances. The cleaning agents are registered with the Federal Office for Environment Protection (Umweltbundesamt) in Berlin.

Requirements

The floor covering may not be warm on account of sunlight or any other heat source. Accordingly, underfloor heating should be switched off well in advance. Before the stone is provided with a protective coating, the covering must be completely dried out and the residual moisture less than 5%. The following rule of thumb applies for the drying period, depending upon the weather conditions and the object at hand: in a thin bed approx. 2-3 weeks, in a mortar bed approx. 4-6 weeks after laying; after cleaning, on the next day at the earliest.

Please pay attention to the information on the product labels and the instructions for use on the specification sheets as well.

Cleaning

initial cleaning/building dirt	AKEMI®'s Ceramics Cement Film Remover	approx. 50-100 m ² /litre
concrete film		
normal dirt	AKEMI®'s Ceramics Intensive Cleaner	approx. 50-100 m ² /litre
dirt layers	AKEMI®'s Ceramics Intensive Cleaner	approx. 50-100 m ² /litre
wax/polymer layers	AKEMI®'s Ceramics Intensive Cleaner	approx. 50-100 m ² /litre
calcareous-/soap scum	AKEMI®'s Disinfectant Cleaner	approx. 100-200 m ² /litre
(bathroom/shower cab)		
joint-cleaning		

Protection - indoors + outdoors

impregnation	not possible	
Care		
regular cleaning	AKEMI®'s Ceramics Care Cleaner	approx. 1000-2000 m ² /litre

Your authorized dealer:



AKEMI GmbH • Lechstraße 28 • D-90451 Nürnberg • Tel. +49 (0) 911/642960 • Fax +49 (0) 911/644456