

Technical Instruction Sheet

page 1 of 2

Properties:

AKEMI®'s Crystallizer Finish AK 2 (product colour: rosé) is a special-purpose liquid product, which is ready to use. It is based on high quality fluorosilicate agents with a well-balanced combination of active agents. The product is characterized by the following properties:

- polish of marble, lime stone, terrazzo, not a coating
- produces high gloss
- reduces the hazard of slipping
- improves the stone surface
- reduces absorption of dirt, therefore easier to take care of
- colour and structure intensification
- easy application
- lowest pollution through noise, dirt and dust during application

Application areas:

AKEMI®'s Crystallizer Finish AK 2 is used to improve the surface and the appearance of new as well as old floor coverings made of limestone (e. g. marble, travertine) or cement-bound cast stone (e. g. terrazzo) which have been pre-treated with AKEMI®'s Basic Crystallizer AK 1.

Instructions for use:

1. Shake well before use.
2. The surface must be clean, dry and free of any coatings.
3. Pre-treatment with AKEMI®'s Basic Crystallizer AK 1 is recommended.
4. Best working temperature: 15 – 25° C; avoid direct sunlight and turn off underfloor heating.
5. Only treat small areas of 2 – 3 m² at a time.
6. Evenly apply approx. 10 – 20 ml/m² of AKEMI®'s Crystallizer Finish AK 2 with a manual pump spray. Immediately afterwards begin polishing crosswise and in circular movements with a heavy, slowly-rotating single-plate machine and a fine steel wool pad. Continue polishing over and beyond the drying phase until the desired degree of lustre has been achieved. Repeat the process one or twice, if necessary.
7. When you have finished, any resulting dust can be swept or vacuumed away.
8. The surface can be walked on immediately after the treatment.
9. AKEMI®'s Mild Stone Soap can be used for general cleaning purposes.

Special notices:

- surfaces or objects (such as furniture) which are not to be treated should be covered up or masked beforehand
- metal objects may react in contact with the product and discolour
- in order to avoid rust stains, it is recommended to use stainless steel pads
- if you interrupt your work, make sure that there is no contact between the steel wool pad and the floor
- change the pads if the degree of soiling requires it
- use a separate pad for each crystallizer
- do not let the product get into direct contact with plants. If this should happen, rinse with water immediately. Neither concentrated nor diluted solutions should get into contact with flora
- Very good durability after approx. 3-4 months on surfaces that are exposed to high stress (e.g. entrance area in hotels). Re-apply latest after 6 months.

Safety notices:

Please refer to the EC safety data sheet

Technical Instruction Sheet

Technical specifications:	coverage:	10 – 20 ml/m ²
	colour:	rosé
	density:	approx. 1.08 g/cm ³
	pH value:	approx. 2
	shelf life:	can be stored for approx. 1 year in the closed original container under cool and frost-free conditions.

Notice:

The above specifications were made on the basis of the present-day stage of technological development as well as the application research of our company. Because the ways and means of application are beyond our control, the manufacturer cannot be made liable for the contents of this specification sheet.