

Technical Instruction Sheet

page 1 of 1

- Characteristics:** AKEMI® 's Graffiti-Remover is free of acids, alkalines and hydrocarbon chlorides and is based on highly-effective solvents which remove aerosol spray graffiti and the like from unprotected mineral bases and other solvent-resistant surfaces. The product has the following particular properties:
- it has excellent solvent and swelling properties when applied to enamels and aerosols paints.
 - because of it's gel-like consistency it is easy to apply on vertical surfaces
 - it does not cause stains resulting from the dispersion of the paint in the stone
 - it is easy to remove with steam
- Field of Application:** AKEMI® 's Graffiti-Remover is a cleaning agent for the removal of graffiti or similar aerosol paints from façades, building, monuments etc. It is especially suitable for all mineral bases such as natural and artificial stone, marble, granite, concrete, bricks, clinker, sand-lime bricks, plaster etc. On Agglo marble which is bound to synthetic resins it is urgently recommended to carry out a test first.
- Instructions for Use:**
1. The surface must be dry.
 2. The best working temperature lies between 10° - 30°C; direct sunshine should be avoided.
 3. The product is to be evenly applied with a paint brush or a spatula.
 4. In order that the product can take effect it must remain on the graffiti for 10 – 15 minutes. The softened paint can then be washed off with warm water. A hot water jet is suited for larger areas. The water from rinsing must be collected and disposed of accordingly to the local authorities waste water regulations.
 5. In particularly hard and stubborn cases a second treatment may be necessary. AKEMI® 's Graffiti-Remover is then to be intensively applied with a scrubbing brush with natural bristles, left for 10-15 minutes in order for the product to take effect and then to be washed off.
 6. After cleaning it is recommendable to treat the surfaces with a coating of AKEMI® 's Anti-Graffiti as a prophylactic measure against further defilement.
- Special Hints:**
- This product acts in contact with painted surfaces aggressively and is not suitable for the cleaning of wood (hazard of swelling) or plastics which react in contact with solvents. In uncertain cases tests should be carried out on an inconspicuous place. The cleaning of vertical surfaces with steam jet should proceed from the top to the bottom. On coarse surfaces with open pores (e.g. fine sandstone) which have not been protected with AKEMI® Anti-Graffiti traces of paint may remain despite intensive cleaning, because the colour pigments have deeply penetrated into the stone.
 - For adequate waste disposal container must be completely emptied.
- Safety Measures:** see EC Safety Data Sheet
- Technical Data:**
- | | |
|------------------|--|
| Coverage: | 500-100g/m ² |
| Colour: | milky-transparent |
| Consistency: | gel-like, stable |
| pH value: | approx. 6 |
| Density at 20°C: | approx. 1g/cm ³ |
| Shelf life: | Storable for approx. 1 year under cool and dry conditions its tightly closed original container. |
- Notice:** The above information is based on the latest stage of technical progress. It is to be considered as a non-binding hint and does not release the user from a performance test, since application, processing and environmental influences are beyond our realm of control.

TIS 05.03