

Technical Instruction Sheet

1/2

- Characteristics:** AKEMI Primer AP 10 is a 1-component primer for Akemi Silicones to improve adhesion.
- Field of Application:** AKEMI Primer AP 10 is used to prime joint flanks before application of Akemi Silicones on porous, absorbent, mineral surfaces such as natural stone, concrete, bricks, wood and cement. Used in areas indoors and outdoors for wall-, floor- and ceiling joints to improve adhesion of silicone sealants.
- Instructions for Use:**
1. Contact areas must be dry, clean and free of dust and grease
 2. Apply with a brush on clean and dry surface depending on porosity and absorptive capacity 1-2 times wet-in-wet.
 3. Protect the treated surfaces against humidity and dust
 4. After open time of 30 – 60 minutes the silicone sealant can be applied.
 5. For adequate waste disposal please empty container completely.
- Special Hints:**
- In order to prevent stains do not apply primer on visible areas.
 - If stored in a cool place shelf life is one year.
 - Tools can be cleaned with Akemi Universal Diluent
- Safety Measures:** see EC Safety Data Sheet
- Notice:** The above information is based on the latest stage of technical progress. It is to be considered as a non-binding hint and does not release the user from a performance test, since application, processing and environmental influences are beyond our realm of control.

Technical Instruction Sheet

2/2

TIS 11/05