

## **Quartz Clean & Care**

## **Technical Instruction Sheet**

page 1 of 1

**Characteristics:** 

AKEMI<sup>®</sup> Quartz Clean & Care is a watery product which contains highly effective, modified organic compounds, combined with cleaning components which do not form layers. The product is supplied in a pump spray bottle. The product has been especially developed for quartz-made stone (Engineered Stone) and is distinguished by the following qualities:

- effectively cleans surface marks
- suitable for daily cleaning and care
- enhances the resistance of quartz surfaces to stubborn accidental marking (e.g. pen stains)
- refreshes the surfaces lustre and features
- fresh & clean fragrance added
- resistant to UV radiation
- tack-free hardening
- foodsafe

Field of Application:

AKEMI<sup>®</sup> Quartz Clean & Care is suited for the daily cleaning and care of kitchen tops, counters and other surfaces of quartz-made stone (such as Caesarstone, Cambria, Silestone, Zodiaq, etc.). Additionally it excellently supports resp. supplements the resistance of Engineered Stone to staining.

Instructions for Use:

- 1. Shake well before use, then remove the cap of the spray nozzle.
- 2. Best working temperature: 15-25°C (59-77°F).
- 3. Spray an even coat on surface to be treated.
- 4. Spread the product with a clean and lint-free cloth, and buff until the surface is evenly polished.

**Special Hints:** 

- A surplus of Quartz Clean & Care may cause blooming or spotting (can be removed with AKEMI® Cleaner I).
- Store the product free from frost.Slight colour enhancement possible.
- For adequate waste disposal container must be completely emptied.

Safety Measures: see EC Safety Data Sheet

**Technical Data:** Colour: colourless to yellowish

Density: approx. 1 g/cm<sup>3</sup>

Shelf life: 1 year approx. if stored in cool place free from frost in its

tightly closed original container.

**Notice:** The above information is based on the latest stage of technical progress. It is to

be considered as a non-binding hint and does not release the user from a performance test, since application, processing and environmental influences

are beyond our realm of control.

Art. No. 11951 TIS 11.06