# **Material Safety Data Sheet**



# Section 1: Product and Company Identification

Product Name: PV 32-Part B (VF 32)

| Sold By:                  | PolyVers International<br>87 Shawnee Avenue<br>Kansas City, KS 66105<br>913.321.9000   |
|---------------------------|--|
| FOR CHEMICAL<br>EMERGENCY | Spill, leak, fire, exposure, or accident, call CHEMTREC day or night<br>Domestic North America 800.424.9300 International 703.527.3887                 |
| Fax Phone:                | 913.321.1490   |
| TSCA Inventory:           | All components of this product are included, or are exempt from inclusion, in the EPA Toxic Substance Control Act (TSCA) Chemical Substance Inventory. |
| Canadian DSL:             | All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List (DSL).                              |

# Section 2: Composition/Information on Ingredients

| Hazardous Components | CAS#     | ACGIH TLV      | OSHA PEL       | <u>% by Wgt</u> |
|----------------------|----------|----------------|----------------|-----------------|
| Benzyl Alcohol       | 100-51-6 | Not Determined | Not Determined | <10%            |
| Alkyl Amine          | *        | Not Determined | Not Determined | >90%            |
|                      | 1 1 1    | 1 (1)          | 1.             |                 |

\*The Specific chemical identity of this component is being held as a trade secret by the supplier.

## Section 3: Hazards Identification

| Emergency Overview:  |   |   |
|--|---|---|
| Routes of Entry:   | Route   | Entry Risk  |
|  | Inhalation  | Possible  |
|  | Ingestion   | Possible  |
|  | Skin Contact  | Possible  |
|  | Eye Contact   | Possible  |
| Potential Health Effects:                                  | Inhalation  | May cause nausea and respiratory tract irritation. May cause respiratory sensitization in susceptible individuals, can cause lung damage. |
|  | Ingestion   | Corrosive and may cause severe and permanent damage to mouth, throat and stomach.   |
|  | Skin Contact  | Corrosive to the skin and may cause sensitization.  |
|  | Eye Contact   | Corrosive to the eyes and may cause severe damage including blindness. Vapors may be irritating.  |
| Acute Health Hazards:                                      | Acute ingestion causes burning of the mouth, throat, and stomach with abdominal pain. Acute inhalation of vapors and mist can cause nasal discharge and pain in the eyes.     |   |
| Chronic Health Hazards:                                    | If misted or at high concentrations, may cause pallor, nausea, anesthetic or narcotic effects.  |   |
| Medical Conditions<br>Generally Aggravated by<br>Exposure: | Skin and eye sensitization. Depending on individual skin sensitivity, chronic or prolonged exposure may result in irritation, blistering, burning and peeling of skin layers. |   |

#### Section 4: First Aid Measures

| Eye Contact:  | Immediately flush with plenty of water for at least 15 minutes. Continue rinse procedure with water while on way to seek medical attention.  |
|---------------|--|
| Skin Contact: | Remove from skin immediately. Rinse with clean water for 20-30 minutes. Use soapy water if needed. If redness, itching, or a burning sensation develops, seek medical attention. Do not use contaminated clothing until thoroughly decontaminated. Discard contaminated shoes. |
| Ingestion:    | Do NOT induce vomiting! Dilute with water and seek medical attention immediately.  |
| Inhalation:   | Move victim to fresh air immediately. Give oxygen and seek medical attention.  |

## Section 5: Fire-Fighting Measures

| Flammable Limits:                      |  |                     |  |
|--|--|---------------------|--|
| Flash Point, (Method<br>Used):         | >235° Fahrenheit (Pe   | ensky Marten Close  | ed)  |
| Autoignition Temperature:              |  |                     |  |
| NFPA Hazard Rating:                    | Health: 3  | Hazard Scale        | Protective Equipment   |
|  | Flammability: 1  | 0=LEAST<br>1=SLIGHT | A=SAFETY GLASSES<br>B=SAFETY GLASSES. GLOVES                   |
|  | Reactivity: 0  | 2=MODERATE          | C=SAFETY GLASSES, GLOVES<br>C=SAFETY GLASSES, GLOVES AND APRON |
|  | Other: D   | 3=HIGH<br>4=EXTREME | D=SAFETY GLASSES, GLOVES, APRON and<br>RESPIRATOR              |
| HMIS Hazard Rating:                    | Health: 3  |                     |  |
|  | Flammability: 1  |                     |  |
|  | Reactivity: ()   |                     |  |
|  | Protection: D  |                     |  |
| Extinguishing Media:                   | Foam/Carbon dioxid   | e/Dry chemical/Wa   | ater fog   |
| Special Fire Fighting<br>Procedures:   | Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products exist. |                     |  |
| Unusual Fire and<br>Explosion Hazards: | Closed containers ma   | ay rupture due to b | uild-up of pressure when exposed to extreme heat.              |
| Hazardous Decomposition<br>Products:   | I  |                     |  |

# Section 6: Accidental Release Measures

Accidental Release Standard hydrocarbon spill procedures apply to this product. Measures:

## Section 7: Handling and Storage

Handling & Storage Precautions: Prevent all skin and eye contact. Avoid breathing vapors. Re-seal partially used containers. Wash with soap and water before eating or drinking.

# Section 8: Exposure Control/Personal Protection

| Ventilation:                               | Adequate ventilation required. Local exhaust may be required in some areas. Special exhausting generally not required. Mechanical exhaust usually adequate. |
|--|---|
| Respiratory Protection:                    | Respiratory masks should be worn at all times when adequate ventilation does not exist. A NIOSH/MSHA respirator is acceptable.                              |
| Eye Protection:                            | Chemical tight goggles; full face shield if splashing is possible.  |
| Skin Protection:                           | Coveralls and impervious foot covering is recommended.  |
| Other Protective Clothing<br>or Equipment: | Use impervious gloves, neoprene or rubber.  |
|  | Good air flow in working area. Eyewash station and safety shower should be available. Gloves and respiratory equipment should be worn at all times.         |

## Section 9: Physical and Chemical Properties

| Appearance:   | Dark Amber            |                |    |
|---|-----------------------|----------------|----|
| Odor:   | Slight                |                |    |
| Physical State:                                       | Liquid                |                |    |
| ph As Supplied:                                       | No Data               |                |    |
| ph (Other):   | No Data               |                |    |
| Boiling Point:  | N/A                   |                |    |
| Melting Point:  | Not determined        |                |    |
| Freezing Point:                                       | Not determined        |                |    |
| Vapor Pressure (mmHg):                                | Not determined        |                |    |
| Vapor Density (Air=1):                                | No Data               |                |    |
| Specific Gravity (Water=1)                            | 1.00 @ 77° Fahrenheit |                |    |
| Evaporation Rate (Butyl<br>Acetate=1):                | No Data               |                |    |
| Solubility in Water:                                  | Partial               |                |    |
| Percent Solids by Weight:                             | 100                   |                |    |
| Percent Volatile<br>(grams/liter):                    | By Weight: $0\%$      | By Volume:     | 0% |
| Volatile Organic<br>Compounds (VOC)<br>(grams/liter): | With Water: $0\%$     | Without Water: | 0% |
| Viscosity:  |                       |                |    |

#### Section 10: Stability and Reactivity

| Stability:                                    | Stable   |
|---|--|
| Conditions to Avoid ( <i>Stability</i> ):     | Avoid excessive heat, open flame, sparks and strong oxidizing agents. Protect from atmospheric moisture. Replace |
| Incompatibility ( <i>Materials</i> to Avoid): | Avoid strong oxidizers, acids.   |
| Hazardous Decomposition or Byproducts:        | Carbon dioxide, carbon monoxide, nitrogen oxides.  |
| Hazardous Polymerization:                     | Will not occur under normal circumstances.   |
| Conditions to Avoid (Polymerization):         | Avoid incompatible reactants, especially strong bases, oxidizing agents and excessive heat or flames.            |

## Section 11: Toxicological Information

Toxicological Information: No Data

#### Section 12: Ecological Information

Ecological Information: No Data

#### Section 13: Disposal Considerations

Waste Disposal Method: Use excess product in an alternate beneficial application. Dispose of according to current local, state and federal regulations. RCRA Hazard Class:

Non-Regulated

## Section 14: Transport Information

#### **U.S. Department of Transportation**

Proper Shipping Name: Polyamines, Liquid, Corrosive, N.O.S., (Polyalkylamines)

Hazard Class: 8

ID Number: UN 2735

Packing Group:

Label Statement:

#### Water Transportation

Proper Shipping Name: Polyamines, Liquid, Corrosive, N.O.S., (Polyalkylamines)

Hazard Class: 8

ID Number: UN 2735

Packing Group:

Label Statement:

#### Air Transportation

Proper Shipping Name: Polyamines, Liquid, Corrosive, N.O.S., (Polyalkylamines)

Hazard Class: 8

ID Number: UN 2735

Packing Group:

Label Statement:

#### **Other Agencies:**

#### Section 15: Regulatory Information

#### **U.S. Federal Regulations**

|                                  | Section 12(b) Export Notification. This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States: There are no TSCA 12(b) Chemicals in this product.   |
|----------------------------------|---|
| Compensation and Liability Act): | CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product: Chemical Name- See Section 2                  |
| and Reauthorization Act):        | This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:  |
| 311/312 Hazard Categories:       | Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard: See Section 3   |
|                                  | This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: Chemical Name- See Section 2  |
|                                  | California Proposition 65. The chemicals(s) noted below and contained in this product are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at <0.1%: There are no proposition 65 chemicals known to exist in this product. |

#### International Regulations:

## Section 16: Other Information

Other Information:

Preparation Information:

Disclaimer:

To the best of our knowledge, the information contained in this MSDS is accurate. It is intended to assist the user in his evaluation of the product's hazards, and safety precautions to be taken in its use. The data in this MSDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.