Material Safety Data Sheet



Section 1: Product and Company Identification

Product Name: Tack Coat

Sold By: **PolyVers International**

> 87 Shawnee Avenue Kansas City, KS 66105

913.321.9000

FOR CHEMICAL EMERGENCY

Spill, leak, fire, exposure, or accident, call CHEMTREC day or night Domestic North America 800.424.9300 International 703.527.3887

Fax Phone: 913.321.1490

TSCA Inventory: All components of this product are included, or are exempt from inclusion, in the EPA Toxic Substance Control

Act (TSCA) Chemical Substance Inventory.

Canadian DSL: All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance

List (DSL).

Section 2: Composition/Information on Ingredients

<u>Hazardous Components</u>	CAS#	ACGIH TLV	<u>OSHA PEL</u>	% by Wgt
Propylene Glycol Methyl Ether	107-98-2			>80
N-Methyl Pyrrolidone	872-50-4			>15
Adhesion Promoter	253083-8			<10

Section 3: Hazards Identification

Emergency Overview:

Routes of Entry: Entry Risk Route

Inhalation Possible Possible Ingestion Skin Contact Possible Possible Eye Contact

Potential Health Effects: Inhalation May cause nausea and respiratory tract irritation. May cause respiratory sensitization

in susceptible individuals.

Ingestion No significant signs or symptoms of any adverse health hazards. **Skin Contact** Product is a slight skin irritant. May cause swelling and redness.

Eye Contact Mild eye irritant. Vapors slightly uncomfortable. Splashes irritating and painful.

Acute Health Hazards: No information is available on the acute health hazards of this product. Based upon data from testing

of similar products, no significant effects are expected.

Chronic Health Hazards: If misted or at high concentrations, may cause pallor, nausea, anesthetic or narcotic effects.

Medical Conditions Generally Aggravated by Exposure:

Skin and eye sensitization. Depending on individual skin sensitivity, chronic or prolonged exposure may result in irritation, blistering, burning and peeling of skin layers.

Carcinogenicity: OSHA: No data ACGIH: No data NTP: No data IARC: No data

Other:

PolyVers International ©2010 Tack Coat MSDS Rev: 11-04-10 Page 1 of 5

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for at least 15 minutes. If redness, itching, or a burning

sensation develops, seek medical attention.

Skin Contact: Remove from skin immediately. Rinse with clean water for 20-30 minutes. Use soapy water if

needed. If redness, itching, or a burning sensation develops, seek medical attention.

Ingestion: Do NOT induce vomiting! Dilute with water and seek medical attention immediately.

Inhalation: Move victim to fresh air immediately. Give oxygen and seek medical attention.

Section 5: Fire-Fighting Measures

Flammable Limits: Not established

Flash Point, (Method

123°F

Used):

Autoignition Temperature: Not established

NFPA Hazard Rating: Health: 1 Hazard Scale Protective Equipment

Flammability: 2 0=LEAST A=SAFETY GLASSES B=SAFETY GLASSES, GLOVES

Reactivity: 1 2=MODERATE C=SAFETY GLASSES, GLOVES AND APRON 3=HIGH D= SAFETY GLASSES, GLOVES , APRON and

Other: D 4=EXTREME RESPIRATOR

HMIS Hazard Rating: Health: 1

Flammability: 2
Reactivity: 1
Protection: D

Extinguishing Media: Foam/Carbon dioxide/Dry Chemical/Halogenated agents. Treat as Class B fire.

Special Fire Fighting Procedures:

rocedures.

Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or

products exist.

Unusual Fire and Explosion Hazards:

Closed containers may rupture due to build-up of pressure when exposed to extreme heat.

Hazardous Decomposition

Products:

Section 6: Accidental Release Measures

Accidental Release Measures:

Avoid contact with material. Persons not wearing appropriate protective equipment should be excluded until the spill is cleaned up. Stop spill at source, pump liquid to salvage container. Remaining liquid may be taken up on clay, diatomaceous earth, or other absorbent. Treat with 3-8% concentration of ammonium hydroxide or 5-10% sodium carbonate. Add 10 parts neutralizing solution/part isocyanate. Let stand 48 hours.

Section 7: Handling and Storage

Handling & Storage

Precautions:

Prevent all skin and eye contact. Avoid breathing vapors. Re-seal partially used containers. Wash with soap and water before eating or drinking. Protect from moisture contamination. Exothermic generation of carbon dioxide may cause dangerous pressure. Keep away from all ignitable sources as well as extreme heat.

Section 8: Exposure Control/Personal Protection

Ventilation: Adequate ventilation required. Local exhaust may be required in some areas. Special exhausting generally not

required. Mechanical exhaust usually adequate.

Respiratory Protection: Respiratory masks should be worn at all times when adequate ventilation does not exist. A NIOSH/MSHA

respirator is acceptable.

Eye Protection: Chemical tight goggles; full face shield if splashing is possible.

Skin Protection: Coveralls and impervious foot covering is recommended.

Other Protective Clothing

or Equipment:

Use impervious gloves, neoprene or rubber.

Work/ Hygienic Practices: Good air flow in working area. Eyewash station and safety shower should be available. Gloves and respiratory

equipment should be worn at all times.

PolyVers International ©2010 Tack Coat MSDS Rev: 11-04-10 Page 2 of 5

Section 9: Physical and Chemical Properties

Clear Appearance:

Odor: Amine Odor Physical State: Liquid N/A

ph As Supplied: ph (Other):

Boiling Point: N/A Melting Point: N/A

Freezing Point:

Vapor Pressure (mmHg): Approx. 10.9 mm Hg

Vapor Density (Air=1):

Specific Gravity (Water=1): $0.92@77^{\circ}F$

Evaporation Rate (Butyl

.071Acetate=1):

Miscible in water Solubility in Water:

Percent Solids by Weight:

Percent Volatile: By Weight: 85% By Volume:

Volatile Organic With Water: Without Water Compounds (VOC):

Molecular Weight:

Viscosity:

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid excessive heat, open flame, sparks and strong oxidizing agents. Protect from atmospheric Avoid (Stability):

moisture. Replace outage with inert dry nitrogen.

Incompatibility (Materials

to Avoid):

Avoid water, acid, base (alkalis, ammonia), alcohols, metal compounds.

or Byproducts:

Hazardous Decomposition Isocyanate vapors or mist, carbon dioxide, carbon monoxide, nitrogen oxides.

Hazardous Polymerization: May occur

Conditions to Avoid (Polymerization):

Avoid incompatible reactants, especially strong bases, water or temperatures over 160° F.

Section 11: Toxicological Information

Toxicological Information: No data

Section 12: Ecological Information

Ecological Information:

When released into the soil, this material may leach into groundwater. When released into the soil, this material may biodegrade to a moderate extent. When released into water, this material is not expected to evaporate significantly. When released into water, this material may biodegrade to a moderate extent. This material has an estimated bioconcentration factor (BCF) of less than 100. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material is expected to have a half-life between 1 and 10 days. When released into the air, this material is expected to be readily removed from the atmosphere by wet deposition.

Section 13: Disposal Considerations

Waste Disposal Method:

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal

PolyVers International ©2010 Tack Coat MSDS Rev: 11-04-10 Page 3 of 5 regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

RCRA Hazard Class: Non-Regulated

Section 14: Transport Information

U.S. Department of Transportation

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (GLYCOL MONOMETHYL ETHER) PG 111

Hazard Class: [[]

ID Number: Un 1993

Packing Group: Label Statement:

Water Transportation

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (GLYCOL MONOMETHYL ETHER) PG 111

Hazard Class: III

ID Number: Un 1993

Packing Group: Label Statement:

Air Transportation

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (GLYCOL MONOMETHYL ETHER) PG 111

Hazard Class: III

ID Number: Un 1993

Packing Group: Label Statement:

Other Agencies:

Section 15: Regulatory Information

U.S. Federal Regulations

TSCA (Toxic Substance Control Act): Section 12(b) Export Notification. This product contains the following chemical

substances subject to the reporting requirements of TSCA 12(b) if exported from the

United States: There are no TSCA 12(b) Chemicals in this product.

Compensation and Liability Act):

CERCLA (Comprehensive Response CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous

substances are contained in this product: Chemical Name- See Section 2

and Reauthorization Act):

SARA Title III (Superfund Amendments This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of

1986 (SARA Title III) and is considered, under applicable definitions, to meet the

following categories:

311/312 Hazard Categories: Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard: See Section 3

313 Reportable Ingredients: This product contains the following substances subject to the reporting requirements of

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986

and 40 CFR Part 372: Chemical Name- See Section 2

State Regulations: California Proposition 65. The chemicals(s) noted below and contained in this product

> are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present

at <0.1%: There are no proposition 65 chemicals known to exist in this product.

International Regulations:

Tack Coat MSDS PolyVers International ©2010 Rev: 11-04-10 Page 4 of 5

Section 16: Other Information

Other Information:

Preparation Information:

Disclaimer:

To the best of our knowledge, the information contained in this MSDS is accurate. It is intended to assist the user in his evaluation of the product's hazards, and safety precautions to be taken in its use. The data in this MSDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

PolyVers International ©2010 Tack Coat MSDS Rev: 11-04-10 Page 5 of 5