MATERIAL SAFETY DATA SHEET

Date: 01-01-09

SECTION 1: PRODUCT IDENTIFICATION

Trade Name: CA-LC25/VT40 Catalyst Manufacturer: PolyVers International

Product #:CA-LC25/VT4087 Shawnee Ave Kansas City, KS 66105Product:CatalystPhone: 913.321.9000

Cert. # 725019-X

Emergency: Spill, leak, fire, exposure, or accident, call CHEMTREC day or night Domestic North America 800.424.9300 International 703.527.3887

SECTION 2: HAZARDOUS INGREDIENTS

Ingredient	CAS No.	Weight	OSHA		ACGIH		Toxicity Data
		%	PEL ppm	TWA ppm	TWA ppm	STEL ppm	LD ₅₀ , oral, rat g/kg
Tertiary Butyl Acetate	540-88-5	<40	200	200	200	200	Nd
Amino Silane	1760-24-3	<50	200	200	220	250	N/A

Notes: *=mg/m3

Suspected Cancer Agents:

None of the above are suspected cancer agents. All ingredients are listed in the TSCA directory.

SECTION 3: PHYSICAL DATA

Boiling Range, 175-300 °F: **Vapor Pressure,** MEK = 70; AS = <5

°F: mm Hg @ 68 °F:

Vapor TBA = Nd; AS = NA (Air =1) **Volatiles,** 0.00 lbs per gallon

Density: % by Weight:

Evaporation TBA = 2.8; AS = NA **Rate:** (Butyl Acetate = 1)

SECTION 4: FIRE AND EXPLOSION DATA

Flammability: OSHA: Flammable DOT Haz Class: 3 UN: TBA = 1123

DOT Packing Gr: II **Extinguishing Media:** Foam, CO2, Dry Chemical

Extinguishing Media: Foam, CO2, Dry Chemical **Flash Point, °F:** 60

TBA = Nd

CA-LC25/VT40 Catalyst 1 of 3

Unusual fire and explosion hazards:

Vapors are heavier than air and may form a layer at ground level. Isolate from heat, electrical equipment, sparks, and open flame. Wear self-contained breathing apparatus. Closed containers may explode when exposed to extreme heat.

SECTION 5: HEALTH AND HAZARD DATA

Entry Routes: Inhalation and skin contact.

Medical Conditions Aggravated/Exposure Effects:

Eyes: Can cause severe irritation, redness, tearing, blurred vision.

Skin: Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis. **Inhaling:** Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness,

weakness, fatique, nausea, headache, possible unconsciousness, and even asphyxiation.

Date: 01-01-09

Swallowing: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

Emergency and First Aid Procedures:

Eyes: Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical

attention.

Skin: Thoroughly wash exposed area with soap and water. Remove contaminated clothing.

Launder contaminated clothing before re-use.

Inhaled: If affected, remove individual to fresh air. If breathing difficulties persist, oxygen should

be administered by qualified personnel. If breathing has stopped, immediately give

artificial respiration. Keep person warm and guiet. Get medical attention.

Swallowed: Do not induce vomiting. Keep person warm, quiet, and get medical attention. Aspiration

of material deep into the lungs due to vomiting can cause chemical pneumonitis which can

be fatal.

SECTION 6: REACTIVITY DATA

Stability: Stable

Conditions to Avoid: Heat, open flame, sparks

Incompatibility (Materials to Avoid): Strong oxidizers

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, hydrogen fluoride

Hazardous Polymerization: Will not occur

SECTION 7: SPILL OR LEAK PROCEDURES

Spills, Leaks: Eliminate all sources of ignition. Use absorbent cleanup materials or

sweep up. Place in separate container.

Waste Disposal: In separate, closed, metal container in accordance with all applicable

regulations.

CA-LC25/VT40 Catalyst 2 of 3

SECTION 8: SPECIAL PROTECTION INFORMATION

Respiratory Protection: NIOSH/MSHA certified respirator. Use air-line respirators in confined or

restricted ventilation areas.

Ventilation: Sufficient ventilation, in volume and pattern, should be provided to keep

air contaminant concentrations below TLV limit.

Protective Gloves: Neoprene or other solvent-resistant material.

Eye Protection: Splash-proof goggles or face shield.

Other Protective Equipment: Full protective clothing and shoe coverings.

Hygienic Practices: Wash thoroughly before eating, smoking, or using restroom. Launder

contaminated clothing before re-use.

SECTION 9: SPECIAL PRECAUTIONS

Handling and Storage: Keep container closed, upright when not in use. Store in cool, dry, well-

ventilated area. Keep away from feed and food products.

Other Precautions: Do not take internally. Avoid prolonged breathing of vapors, spray mist,

or dust. Avoid contact with skin and eyes. Chronic overexposure to MEK has been reported to cause kidney and liver damage in laboratory

Date: 01-01-09

animals.

CA-LC25/VT40 Catalyst 3 of 3